

# WE MAKE THINGS MOVE!



Hammerhead Trolley  
20,000 lbs. capacity



AC Electric Winch with  
AutoAdvance Line Spooler



Contractor Hoist Package  
2,000 lbs. capacity



HC1500 AC Hoist  
1,500 lb. capacity



HS1-3500-P  
3,500 lbs. capacity



10AAM Davit  
with Manual Hoist  
2,000 lbs. capacity

[www.AlliedPower.com](http://www.AlliedPower.com)  
Tel 503.626.0654  
Beaverton, Oregon

**ALLIED POWER PRODUCTS, INC.**  
**THE WINCH & HOIST SPECIALISTS**

world-class organization. We always strive to produce our products at an extremely high level of quality and performance. This recognition award from Boeing reinforces our commitment to excellence,” said Phil Chant, Chant’s President.

For the 2016 award period, Boeing recognized 480 suppliers who achieved superior performance and quality. Chant Engineering is pleased to be included in this distinguished group, and particularly honored to be named among the-Top 82 suppliers who were awarded the Gold Level of Recognition!

## Modulift provides below-the-hook solution for bedroom installations

Two pioneers in modular concepts of different kinds combined to install bedrooms at the citizenM Tower of London Hotel, which offer guests views of the River Thames, Tower Bridge and a series of other famous landmarks.

Below-the-hook equipment manufacturer Modulift, a specialist provider of modular spreader beams, supplied rigging equipment as Polcom Modular installed 260 pre-fabricated structural modular bedrooms at the iconic riverside new-build.

Modular construction is fast becoming a building method of choice for organizations looking for rapid project completion, assured quality standards and minimal impact on the environment or the local area, said Ben Paget, Structural Director at Polcom. Polcom accepted

a scope of work to design, manufacture, supply and install the bedrooms over an 11-week period, all at night.

The modules had bespoke designed lifting eyes integrated into the structural framing that were utilized by the

*continued on next page*



Polcom originally tested the rig in a one-over-two-over-four configuration but height restrictions onsite meant it had to proceed with either single or one-over-two configurations.